



**Prodital Italia S.r.l.**  
Via Leonardo da Vinci, 34 - 36071 Arzignano (VI) Italy  
Tel. +39.0444.482354 – Fax. +39.0444.482589



# NABUCCO

Technical specification

		RESULT	ISO PARAMETERS
Description:	European cowhide aniline dyed		
Size:	Full hide (4,80-5,20 SqMt)		
Finishing:	Nabuk leather		
Thickness:	1.2-1.3 mm		
Light Fastness:	ISO 105- B02	3-4 blue scale	≥3 blue scale
Flex:	ISO 5402	20.000 cycles, No cracks	20.000 cycles, No cracks
Adesion to finish:	ISO 11644	N/A	N/A
Color Fastness:	ISO 11640/ 11641	50 cycles, 5	50 cycles, ≥3
to rubbing:		20 cycles, 4-5	20 cycles, ≥3
Color Fastness to water spotting:	ISO 15700	5 grey scale	≥3 grey scale
Cold crack temperature of surface coating:	ISO 17233, -15°	N/A	N/A
Formaldehyde:	ISO 17226-1	≤7,3 mg/kg	≤150 ppm
Flammability:	UNI EN 1021-1	Complies	Complies
	(BS 5852 part 1)		
Country of origin:	Italy		
Cleaning instruction			
For ordinary cleaning use a special cloth for Nabuk leather and wind it around with a dry and soft sponge. For stains removal you may use a cleaning set according to reported instructions. Never use abrasive or aggressive products like solvents, stain removers. Never steam it and don't use shoes cleaning products.			
Rev. 1			